


# 350 DRILL BIT FOR TIMBERING, ROUND SHANK



## DRIVE



## EXECUTION

- Made of wear resistant CV steel
- Long tool life due to special alloying
- Offset shank with open spiral outfall prevents from drill bit getting jammed
- Optimal true running accuracy as well as chip removal also in deep holes


## FOR USE IN



## APPLICATION

- In all rotary and percussion drilling machines
- To break through outer and inner covering boards in one operation
- Only for rotary use
- Also with concrete leftovers

## PACKAGING



≥ 28 mm

[167]

D Ø mm	D Ø"	L2 mm	L1 mm	d Ø mm		EAN 4016707...	 12345
6,0	1/4	100	400	6,0	1	030130	350 060 400
6,0	1/4	100	600	6,0	1	030000	350 060 600
8,0	5/16	100	400	8,0	1	030017	350 080 400
8,0	5/16	100	600	8,0	1	030208	350 080 600
8,0	5/16	100	800	8,0	1	030710	350 080 800
10,0	3/8	100	400	8,0	1	030024	350 100 400
10,0	3/8	100	600	8,0	1	030215	350 100 600
10,0	3/8	100	800	8,0	1	030727	350 100 800
12,0	15/32	100	400	10,0	1	030031	350 120 400
12,0	15/32	100	600	10,0	1	030222	350 120 600
12,0	15/32	100	800	10,0	1	030734	350 120 800
14,0	9/16	100	400	10,0	1	030048	350 140 400
14,0	9/16	100	600	10,0	1	030239	350 140 600
14,0	9/16	100	800	10,0	1	030741	350 140 800
16,0	5/8	100	400	10,0	1	030055	350 160 400
16,0	5/8	100	600	10,0	1	030246	350 160 600
16,0	5/8	100	800	10,0	1	030758	350 160 800
18,0	11/16	100	400	13,0	1	030062	350 180 400
18,0	11/16	100	600	13,0	1	030253	350 180 600
18,0	11/16	100	800	13,0	1	030765	350 180 800
20,0	3/4	100	400	13,0	1	030079	350 200 400
20,0	3/4	100	600	13,0	1	030260	350 200 600
20,0	3/4	100	800	13,0	1	030772	350 200 800
22,0	7/8	100	400	13,0	1	030086	350 220 400
22,0	7/8	100	600	13,0	1	030277	350 220 600
22,0	7/8	100	800	13,0	1	030789	350 220 800
24,0	15/16	100	400	13,0	1	030093	350 240 400
24,0	15/16	100	600	13,0	1	030284	350 240 600
26,0	1 1/32	100	400	13,0	1	030109	350 260 400

## Comments

- Largest clamping shank (d) 13 mm Ø
- Other dimensions on request

# 355 SDS-PLUS DRILL BIT FOR TIMBERING



## DRIVE



## EXECUTION

- Made of wear resistant CV steel
- Long tool life due to special alloying
- Offset shank with open spiral outfall prevents from drill bit getting jammed
- Optimal true running accuracy as well as chip removal also in deep holes

## FOR USE IN



## APPLICATION

- Fits directly into all hammer drilling machines with SDS-plus and HILTI TE-C drive
- Only for rotary use
- To break through outer and inner covering boards in one operation
- Also with concrete leftovers
- Adapters for SDS-plus [36]

## PACKAGING



### Comments

- Other dimensions on request

D Ø mm	D Ø "	L2 mm	L1 mm	d Ø mm		EAN 4016707...	
10,0	3/8	100	400	10,0	1	030406	355 100 400
10,0	3/8	100	600	10,0	1	030604	355 100 600
12,0	15/32	100	400	10,0	1	030413	355 120 400
12,0	15/32	100	600	10,0	1	030611	355 120 600
12,0	15/32	100	800	10,0	1	030963	355 120 800
14,0	9/16	100	400	10,0	1	030420	355 140 400
14,0	9/16	100	600	10,0	1	030628	355 140 600
14,0	9/16	100	800	10,0	1	030970	355 140 800
16,0	5/8	100	400	10,0	1	030437	355 160 400
16,0	5/8	100	600	10,0	1	030635	355 160 600
16,0	5/8	100	800	10,0	1	030987	355 160 800
18,0	11/16	100	400	10,0	1	030444	355 180 400
18,0	11/16	100	600	10,0	1	030642	355 180 600
18,0	11/16	100	800	10,0	1	030994	355 180 800
20,0	3/4	100	400	10,0	1	030451	355 200 400
20,0	3/4	100	600	10,0	1	030659	355 200 600
20,0	3/4	100	800	10,0	1	031007	355 200 800
22,0	7/8	100	400	10,0	1	030468	355 220 400
22,0	7/8	100	600	10,0	1	030666	355 220 600
22,0	7/8	100	800	10,0	1	031014	355 220 800
24,0	15/16	100	400	10,0	1	030475	355 240 400
24,0	15/16	100	600	10,0	1	030673	355 240 600